


Order Code:

- Silver [RAL 9006] 21001
- White [RAL 9010] 21002
- Black [RAL 9005] 21003
- Custom Finishes Available on Request


Optional Extras (specify when ordering):

- DMX Control Conversion 11211
- DALI Control Conversion 11222
- Sequencing Conversion 11233



Construction Mounting

- Lamp Type**
- Lamp Power**
- Beam Width**
- Voltage**
- Transformer**
- Internal Dimmer**
- External Dimmer**
- Place of Use**
- Movement**
- Finish**
- Weight**
- Sequencing**
- Control Options**

Die-cast aluminium housing, powder coated
 3-Circuit track compatible with the Eutrac 3-Circuit Adaptor (other adaptors can be fitted as a custom order)
 QR111
 100W Max; 12V
 4° - 45°, lamp dependant
 220-240V; 50/60Hz¹
 Integral electronic transformer 105VA
 Internal dimmer 0-100%; leading edge
 External dimmer can also be used²
 Interior use only
 360° Pan; +/- 90° Tilt
 Silver RAL 9006, White RAL 9010, Black RAL 9005
 1.3kg (including lamp)
 Available (11233)
 1. Handheld remote (11400)
 2. DMX (11211)
 3. DALI (11222)



12V 50W 4°		QR111
1m	0.07m	40000 lx
2m	0.14m	10000 lx
3m	0.20m	4500 lx
4m	0.28m	2500 lx
5m	0.34m	1600 lx



12V 100W 45°		QR111
1m	0.83m	2800 lx
2m	1.66m	700 lx
3m	2.50m	310 lx
4m	3.30m	175 lx
5m	4.15m	110 lx

Notes

¹50Hz as standard. For 60Hz, specify when ordering.
²If external dimmer is used, the lamp dims normally, motors operate down to 50% dimming. If the internal dimmer is used at the same time, the dimmer with the lowest setting dominates.

If you are in doubt as to the suitability or compatibility of this product, contact RCL.

Photometric data is provided as a guide only. Check with lamp manufacturers for latest data.

