


Order Code:

- Silver [RAL 9006] **21005**
- White [RAL 9010] **21006**
- Black [RAL 9005] **21007**
- Custom Finishes Available on Request


Optional Extras (specify when ordering):

- DMX Control Conversion 11211**
- DALI Control Conversion 11222**
- Sequencing Conversion 11233**



Construction Mounting

- Lamp Type**
- Lamp Power**
- Beam Width**
- Voltage**
- Transformer**
- Internal Dimmer**
- External Dimmer**
- Place of Use**
- Movement**
- Finish**
- Weight**
- Sequencing**
- Control Options**

Die-cast aluminium housing, powder coated
 3-Circuit track compatible with the Eutrac 3-Circuit Adaptor (other adaptors can be fitted as a custom order)
 QR-CBC51
 75W Max; 12V
 10° - 60°, lamp dependant
 220-240V; 50/60Hz¹
 Integral electronic transformer 75VA
 Internal dimmer 0-100%; leading edge
 External dimmer can also be used²
 Interior use only
 360° Pan; +/- 90° Tilt
 Silver RAL 9006, White RAL 9010, Black RAL 9005
 1.3kg (including lamp)
 Available (11233)
 1. Handheld remote (11400)
 2. DMX (11211)
 3. DALI (11222)



Distance (m)	Beam Diameter (m)	Illuminance (lx)
1m	0.18m	12500 lx
2m	0.35m	3125 lx
3m	0.52m	1389 lx
4m	0.70m	781 lx
5m	0.88m	500 lx



Distance (m)	Beam Diameter (m)	Illuminance (lx)
1m	1.15m	1430 lx
2m	2.31m	358 lx
3m	3.46m	159 lx
4m	4.62m	89 lx
5m	5.77m	57 lx

Notes

¹50Hz as standard. For 60Hz, specify when ordering.
²If external dimmer is used, the lamp dims normally, motors operate down to 50% dimming. If the internal dimmer is used at the same time, the dimmer with the lowest setting dominates.

If you are in doubt as to the suitability or compatibility of this product, contact RCL.

