


Order Code:


- Silver [RAL 9006] 21009
- White [RAL 9010] 21010
- Black [RAL 9005] 21011
- Custom Finishes Available on Request

Optional Extras (specify when ordering):


- DMX Control Conversion 11211
- DALI Control Conversion 11222
- Sequencing Conversion 11233


Construction Mounting
**Lamp Type
Lamp Power
Beam Width
Voltage
Ballast
Dimming**
**Place of Use
Movement
Finish
Weight
Sequencing
Control Options**

Die-cast aluminium housing, powder coated
 3-Circuit track compatible with the Eutrac 3-Circuit Adaptor (other adaptors can be fitted as a custom order)
 HIR111-CE-P
 35W
 10° - 40°, lamp dependant
 220-240V; 50/60Hz¹
 Internal 35W
 Not currently available for metal halide lamps²
 Interior use only
 360° Pan; +/- 90° Tilt
 Silver RAL 9006, White RAL 9010, Black RAL 9005
 1.3kg (including lamp)
 Available (11233)
 1. Handheld remote (11400)
 2. DMX (11211)
 3. DALI (11222)
 DMX or DALI requires setup (with additional costs) and must be specified when ordering. The DMX/DALI signals must be supplied via Eutrac track with data bus.



Distance (m)	Beam Diameter (m)	Beam Area (m²)	Illuminance (lx)
1m	0.18m	0.0324	35000 lx
2m	0.35m	0.1225	8750 lx
3m	0.52m	0.2704	3890 lx
4m	0.70m	0.49	2190 lx
5m	0.88m	0.7744	1400 lx



Distance (m)	Beam Diameter (m)	Beam Area (m²)	Illuminance (lx)
1m	0.7m	0.49	4000 lx
2m	1.40m	1.96	1000 lx
3m	2.00m	4.00	445 lx
4m	2.80m	7.84	250 lx
5m	3.50m	12.25	160 lx

Notes

¹50Hz as standard. For 60Hz, specify when ordering.
²Luminaire can be switched on/off.

If you are in doubt as to the suitability or compatibility of this product, contact RCL.

