


**Order Code:**

- Silver [RAL 9006] 21041
- White [RAL 9010] 21042
- Black [RAL 9005] 21043
- Custom Finishes Available on Request


**Optional Extras (specify when ordering):**

- DMX<sup>512</sup>** DMX Control Conversion 11211
- DALI** DALI Control Conversion 11222
- ∞ Sequencing Conversion 11233



**Construction**

- Mounting**
- Lamp Type**
- Lamp Power**
- Beam Width**
- Voltage**
- Transformer**
- Internal Dimmer**
- External Dimmer**
- Place of Use**
- Movement**
- Finish**
- Weight**
- Sequencing**
- Control Options**

Die-cast aluminium housing, powder coated  
 1-Circuit track compatible with the Eutrac 1-Circuit Adaptor QR-CBC51  
 75W Max; 12V  
 10° - 60°, lamp dependant  
 220-240V; 50/60Hz<sup>1</sup>  
 Integral electronic transformer 75VA  
 Internal dimmer 0-100%; leading edge  
 External dimmer can also be used<sup>2</sup>  
 Interior use only  
 360° Pan; +/- 90° Tilt  
 Silver RAL 9006, White RAL 9010, Black RAL 9005  
 1.3kg (including lamp)  
 Available (11233)  
 1. Handheld remote (11400)  
 2. DMX (11211)  
 3. DALI (11222)  
 DMX or DALI requires setup (with additional costs) and must be specified when ordering. The DMX/DALI signals must be supplied via Eutrac track with data bus.



| Distance (m) | Beam Diameter (m) | Beam Area (m²) | Illuminance (lx) |
|--------------|-------------------|----------------|------------------|
| 1m           | 0.18m             | 0.0324         | 12500 lx         |
| 2m           | 0.35m             | 0.1225         | 3125 lx          |
| 3m           | 0.52m             | 0.2704         | 1389 lx          |
| 4m           | 0.70m             | 0.49           | 781 lx           |
| 5m           | 0.88m             | 0.7744         | 500 lx           |



| Distance (m) | Beam Diameter (m) | Beam Area (m²) | Illuminance (lx) |
|--------------|-------------------|----------------|------------------|
| 1m           | 1.15m             | 1.3225         | 1430 lx          |
| 2m           | 2.31m             | 5.3421         | 358 lx           |
| 3m           | 3.46m             | 11.9716        | 159 lx           |
| 4m           | 4.62m             | 21.3444        | 89 lx            |
| 5m           | 5.77m             | 33.2929        | 57 lx            |

**Notes**

<sup>1</sup>50Hz as standard. For 60Hz, specify when ordering.  
<sup>2</sup>If external dimmer is used, the lamp dims normally, motors operate down to 50% dimming. If the internal dimmer is used at the same time, the dimmer with the lowest setting dominates.

If you are in doubt as to the suitability or compatibility of this product, contact RCL.

