


**Order Code:**

- Silver [RAL 9006] 21073
- White [RAL 9010] 21074
- Black [RAL 9005] 21075
- Custom Finishes Available on Request

**Optional Extras (specify when ordering):**

- DMX<sup>512</sup>** DMX Control Conversion 11211
- DALI** DALI Control Conversion 11222
- ∞ Sequencing Conversion 11233


**Construction**
**Mounting**
**Lamp Type**
**Lamp Power**
**Beam Width**
**Voltage**
**Transformer**
**Internal Dimmer**
**External Dimmer**
**Place of Use**
**Min. Ceiling Clearance**
**Max. Ceiling Thickness**
**Ceiling Cutout**
**Movement**
**Finish**
**Weight**
**Sequencing**
**Control Options**

Die-cast aluminium housing, powder coated

Monopoint

QR111

100W Max; 12V

4° - 45°, lamp dependant

 220-240V; 50/60Hz<sup>1</sup>

Integral electronic transformer 105VA

Internal dimmer 0-100%; leading edge

 External dimmer can also be used<sup>2</sup>

Interior use only

100mm

20mm

Ø70 - 75mm

360° Pan; +/- 90° Tilt

Silver RAL 9006, White RAL 9010, Black RAL 9005

1.5kg (including lamp)


Available (11233)

1. Handheld remote (11400)


2. DMX (11211)

3. DALI (11222)

DMX or DALI requires setup (with additional costs) and must be specified when ordering.



12V 50W 4°	QR111
1m 0.07m	40000 lx
2m 0.14m	10000 lx
3m 0.20m	4500 lx
4m 0.28m	2500 lx
5m 0.34m	1600 lx



12V 100W 45°	QR111
1m 0.83m	2800 lx
2m 1.66m	700 lx
3m 2.50m	310 lx
4m 3.30m	175 lx
5m 4.15m	110 lx

**Notes**
<sup>1</sup>50Hz as standard. For 60Hz, specify when ordering.

<sup>2</sup>If external dimmer is used, the lamp dims normally, motors operate down to 50% dimming. If the internal dimmer is used at the same time, the dimmer with the lowest setting dominates.

If you are in doubt as to the suitability or compatibility of this product, contact RCL.

