


Order Code:

- Silver [RAL 9006] 21113
- White [RAL 9010] 21114
- Black [RAL 9005] 21115
- Custom Finishes Available on Request

Optional Extras (specify when ordering):

- DMX512** DMX Control Conversion 11211
- DALI** DALI Control Conversion 11222
- ∞ Sequencing Conversion 11233


Construction

- Mounting** Hook Clamp
- Barrel Bar Diameter** Ø40 - 50mm
- Lamp Type** QR-CBC51
- Lamp Power** 75W Max; 12V
- Beam Width** 10° - 60°, lamp dependant
- Voltage** 220-240V; 50/60Hz¹
- Transformer** Integral electronic transformer 75VA
- Internal Dimmer** Internal dimmer 0-100%; leading edge
- External Dimmer** External dimmer can also be used²
- Place of Use** Interior use only
- Movement** 360° Pan; +/- 90° Tilt
- Finish** Silver RAL 9006, White RAL 9010, Black RAL 9005
- Weight** 1.6kg (including lamp)
- Sequencing** Available (11233)
- Control Options**
 1. Handheld remote (11400)
 2. DMX (11211)
 3. DALI (11222)

Die-cast aluminium housing, powder coated

Hook Clamp

Ø40 - 50mm

QR-CBC51

75W Max; 12V

10° - 60°, lamp dependant

 220-240V; 50/60Hz¹

Integral electronic transformer 75VA

Internal dimmer 0-100%; leading edge

 External dimmer can also be used²

Interior use only

360° Pan; +/- 90° Tilt

Silver RAL 9006, White RAL 9010, Black RAL 9005

1.6kg (including lamp)

Available (11233)


1. Handheld remote (11400)

2. DMX (11211)


3. DALI (11222)

DMX or DALI requires setup (with additional costs) and

must be specified when ordering.



Distance (m)	Beam Diameter (m)	Illuminance (lx)
1m	0.18m	12500 lx
2m	0.35m	3125 lx
3m	0.52m	1389 lx
4m	0.70m	781 lx
5m	0.88m	500 lx



Distance (m)	Beam Diameter (m)	Illuminance (lx)
1m	1.15m	1430 lx
2m	2.31m	358 lx
3m	3.46m	159 lx
4m	4.62m	89 lx
5m	5.77m	57 lx

Notes
¹50Hz as standard. For 60Hz, specify when ordering.

²If external dimmer is used, the lamp dims normally, motors operate down to 50% dimming. If the internal dimmer is used at the same time, the dimmer with the lowest setting dominates.

If you are in doubt as to the suitability or compatibility of this product, contact RCL.

