


**Order Code:**

- Silver [RAL 9006] 21117
- White [RAL 9010] 21118
- Black [RAL 9005] 21119
- Custom Finishes Available on Request

**Optional Extras (specify when ordering):**

- DMX512** DMX Control Conversion 11211
- DALI** DALI Control Conversion 11222
- ∞ Sequencing Conversion 11233


**Construction**

- Mounting** Hook Clamp
- Barrel Bar Diameter** Ø40 - 50mm
- Lamp Type** HIR111-CE-P
- Lamp Power** 35W
- Beam Width** 10° - 40°, lamp dependant
- Voltage** 220-240V; 50/60Hz<sup>1</sup>
- Ballast** Internal 35W
- Dimming** Not currently available for metal halide lamps<sup>2</sup>
- Place of Use** Interior use only
- Movement** 360° Pan; +/- 90° Tilt
- Finish** Silver RAL 9006, White RAL 9010, Black RAL 9005
- Weight** 1.6kg (including lamp)
- Sequencing** Available (11233)
- Control Options**
  1. Handheld remote (11400)
  2. DMX (11211)
  3. DALI (11222)

Die-cast aluminium housing, powder coated

Hook Clamp

Ø40 - 50mm

HIR111-CE-P

35W

10° - 40°, lamp dependant

 220-240V; 50/60Hz<sup>1</sup>

Internal 35W

 Not currently available for metal halide lamps<sup>2</sup>

Interior use only

360° Pan; +/- 90° Tilt

Silver RAL 9006, White RAL 9010, Black RAL 9005

1.6kg (including lamp)

Available (11233)

1. Handheld remote (11400)

2. DMX (11211)


3. DALI (11222)

DMX or DALI requires setup (with additional costs) and must be specified when ordering.


**Notes**
<sup>1</sup>50Hz as standard. For 60Hz, specify when ordering.

<sup>2</sup>Luminaire can be switched on/off.

If you are in doubt as to the suitability or compatibility of this product, contact RCL.



Distance (m)	Beam Diameter (m)	Illuminance (lx)
1m	0.18m	35000 lx
2m	0.35m	8750 lx
3m	0.52m	3890 lx
4m	0.70m	2190 lx
5m	0.88m	1400 lx



Distance (m)	Beam Diameter (m)	Illuminance (lx)
1m	0.7m	4000 lx
2m	1.40m	1000 lx
3m	2.00m	445 lx
4m	2.80m	250 lx
5m	3.50m	160 lx

Photometric data is provided as a guide only. Check with lamp manufacturers for latest data.

